

NEXEDGE

The Ultimate Digital Communication



NX-620

4G LTE Network IP Radio

- Dialling Function
- Voice Recording
- Built in GPS
- Noise Cancellation
- Group & Private Call
- OTAP – Over The Air Programming
- ICCID Login
- Nationwide Coverage



Specification

NX-620

|                                        |
|----------------------------------------|
| Operation system: RTOS                 |
| Language: English                      |
| Working voltage: 3.7V                  |
| Display: 1.77inch, resolution: 160*128 |
| Battery: 3800mAh                       |
| Antenna: built-in antenna              |
| Speaker: 8Ω, 1.5W                      |
| Audio output power: 2W@10% distortion  |
| Max. output power: 23dBm±2dBm@Alupbts  |
| Rx sensibility: -106dbm                |
| Charger: type-c cable                  |
| Earphone: K-connector                  |
| Size: 124*58*28mm                      |
| Weight: 175g                           |
| Working temperature: -20-+60°C         |
| Storage temperature: -20-+60°C         |

| 3GPP        | Tx           | Rx           |
|-------------|--------------|--------------|
| LTE-FDD B1  | 1920-1980MHz | 2110-2170MHz |
| LTE-FDD B3  | 1710-1785MHz | 1805-1880MHz |
| LTE-FDD B5  | 824-849MHz   | 869-894MHz   |
| LTE-FDD B8  | 880-915MHz   | 925-960MHz   |
| LTE-FDD B34 | 2010-2025MHz | 2010-2025MHz |
| LTE-TDD B38 | 2570-2620MHz | 2570-2620MHz |
| LTE-FDD B39 | 880-1920MHz  | 1880-1920MHz |
| LTE-TDD B40 | 2300-2400MHz | 2300-2400MHz |
| LTE-TDD B41 | 2535-2675MHz | 2535-2675MHz |

Accessory



Battery



Adapter



Type-C cable



Belt clip



SCAN ME

NEXEDGE SOLUTIONS  
22A-2 Wangsa Biz Avenue,  
Jln Wangsa Niaga Off Jln 34/26  
53300 Kuala Lumpur  
+603 4820 8118

Dealer

CE FC RoHS